

WALL PRIMER



TECHNICAL DATASHEET

January 2013

Cancels and replaces all previous datasheets

INTERIOR

DESCRIPTION AND DESTINATION OF PRODUCT

Description:	Water-based primer with acrylic copolymers
Destination:	Enhances adherence / optimises the rendering of WALL MATT, LACK MATT and WALL & WOOD SATIN, thanks to its smooth look. New or refurbishment works
Properties:	Quick drying, odourless Microporous Insaponifiable Very opacifying
Classification:	AFNOR NF T 36-005: Family I – Class 7b2 According to NFT 30-804 and P 84403

TECHNICAL INFORMATION

Appearance in Tin:	Unctuous paint
Density:	1.4 kg/L
Dry matter:	In volume: 34 % In weight: 55 %
VOC:	Limit value for this product in the EU (cat. A/a): 30 g/l (2010). This product contains a maximum of 29 g/L VOC
Finished look:	Semi-smooth
Specular gloss:	< 5 at 85°, matt
Coverage:	about 10 to 12m ² /L, depending on the nature of the base and the method of application (According to the NF T 30-073 standard)
Drying time: (at 20°C and 65% R.H.)	Dust-free: 1 hour Dry: 4 hours Recoatable: 8 hours
Tints:	128 tints in colour chart <i>In order to know which undercoat to use for the paint chosen, ask for your retailer's advice</i>
Packaging:	2.5 L and 5 L
Conservation:	12 months in unopened original packaging Keep away from frost and heat

WALL PRIMER

APPLICATION TIPS

Dilution: Brush, roller: Dilution possible up to 10% water depending on support and smoothness desired

Preparation of product: Mix before use

Application material: Brush, special acrylic roller
Spraygun

Cleaning of tools: Water

Conditions of application: According to DTU 59.1

Bases: Unstructured, condition and quality according to DTU 59.1

- Uncoated: Interior:
Non-hydrophobic and/or non-powdery by-products and plaster.
Hydraulic binder-based supports
Wood and wood by-products, except wood with a particular behaviour (teak, iroko, afzelia, western red cedar, etc.)
- Coated: Above supports coated with an old adhesive paint
For other supports, please consult us

Preparation of bases: According to good practice and DTU 59.1 to which special preparations are added:

- Interior and exterior supports: Wood and by-products: Degrease with EPOXY THINNER before this base coat
- Interior coated bases: Sand down glossy or satin surfaces
- Exterior supports: Decontaminate support with ANTI-FOAM

Systems of application:

According to DTU 59.1, priming should be envisaged according to the state of finish desired

Bases	Interiors: Wood and by-products / Other compatible supports and bases	Protected exteriors: Untreated / Coated
Primer	1 coat of WALL PRIMER after preparation of support	1 coat of WALL PRIMER after preparation of support
Finish	2 coats of WALL MATT LACK MATT or WALL&WOOD SATIN	2 coats of LACK MATT

Precautions for use: Do not apply in excess
Apply on dry support

Health and safety: Product classified as non-hazardous
See safety datasheet

The physical and chemical details contained in this sheet are valid for the white product.
The VOC value indicated represents the value of the ready-to-use product, after colour mixing, dilution, etc., with the products from our range. Under no circumstance can we be deemed liable for mixtures made with other commercial products whose real VOC content we are not aware of.
The aim of this technical datasheet is to inform our customers on the properties of our product. The information contained therein is based on our current knowledge. We prompt our customers to check the suitability of the product for the type and condition of the bases and to conduct representative tests. It is our customers' responsibility to check that this datasheet has not been replaced with, or updated by a more recent version.

MATERIS PEINTURES S.A.S. with a share capital of €6,236,973
71, Boulevard du Général Leclerc – 92583 Clichy Cedex - Tel: 01.41.27.64.20 – Fax: 01.41.27.64.21
RCS Nanterre B 592 028 294 – <http://www.materis-paints.com>