



ATS ELECTRO-LUBE
INTERNATIONAL INCORPORATED

MD2000 TITAN CL™

Automatic Lubricator

≈ WIND ≈ SERIES

The **MD2000 TITAN CL™ CARTRIDGE LUBER**.....
a powerful, motor-driven automatic lubricator which is refillable
by simply replacing a standard grease cartridge.

Its microprocessor controlled, energy efficient motor delivers
grease to a fixed displacement pump which produces pressures up
to 900psi. This strength allows the **TITAN CL™** to drive lubricant
to several bearings consecutively through long feed lines using a
progressive distribution block.



Features

- Most powerful lubricator on the market; produces up to 900psi which enables it to service single-point applications up to 30' away (9m.) and multi-point applications up to 20' (6m.) away.
- Available with long-life replaceable battery packs or **optional** external power sources. (AC and DC)
- Single or Multi-point configuration.
- Refillable using a standard grease cartridge (no other tools needed).
- Able to service up to 12 lube points with **optional** progressive distribution block.
- Unit is mounted on an easy to install base plate.
- **Optional** remote control available to connect to customer supplied equipment or machinery. (eg: PLC, contactors, relays)
- Suitable for both land-based or off-shore Nacelles.
- Multiple settings from 15 days to 2 years.
- Built on proven technology used worldwide since 1982.
Market Leader
- Designed for the toughest operating environments.

Temperature Range:

5°F to + 132°F (-15°C to + 55°C)

(NOTE: Low Temp lubricants
must be used at low temperatures)

Size:

Model WTCL

24-1/2" H X 6" W X 8" D

(62cm H x 15cm W x 20cm D)



www.atselectrolube.com

BUS: (604) 946-1308 FAX: (604) 946-0427 TOLL FREE PHONE: 1-800-663-8141 TOLL FREE FAX: 1-800-663-8140
7388 Wilson Avenue, Delta, British Columbia, Canada V4G 1H3