



3000.00 ±25.00 [118.110 ±0.984]

80.00 [3.150]

230.00 [9.055]

$\phi 18.00 [0.709]$
 $\phi 18.00 [0.709]$
 $\phi 12.00 [0.472]$
 $\phi 76.20 [3.000]$
 20.00 [0.787]
 65.00 [2.559]
 70.00 [2.756]

$\phi 35.00 \pm 5.00 [1.378 \pm 0.197]$

2.00 [0.079]
 16.00 [0.630]

DETAIL B
SCALE 1 : 1

a3 connecting area closed welded

SECTION A-A

ADDITIONAL SPECIFICATIONS
 ANCHOR TUBE:
 PIPE: STEEL TUBE, ROUND,
 PER ASTM A500 GRADE B/C Fy=350MPa (50ksi) Min

WING:
 WING PLATE: MAT'L ASTM A1011 GRADE 33;
 Min Fy=230MPa(33ksi)

ALL WELDING ACCORDING TO CSA STANDARD W59-03

GALVANIZED TO ASTM A123/A123M-02



DWG NO: 0005-108-76-4.2-3000		REV. -
DRAWN: C.SENIS	DIMENSIONS : INCHES TOLERANCES: FRACTIONAL: ± 1/32 ANGULAR: ±1° 0.00: ± 0.015 0.000: ± 0.005 0.0000: ± 0.0005	
DATE: 7/5/2016	SCALE: 1:3	SIZE B
131 LAKE ROAD, BOWMANVILLE, ONT. CANADA, L1C 4P8		SHEET 1 OF 1