



3000.00 ±25.00 [118.110 ±0.984]

80.00 [3.150]

230.00 [9.055]

Ø 76.20 [3.000]

4.19 [0.165]

20.00 [0.787]

Ø 18.00 [0.709]

Ø 12.00 [0.472]

70.00 [2.756]

65.00 [2.559]

4.00 [0.157]

Ø 176.00 [6.929]

C (1 : 5)

DETAIL B  
SCALE 1 : 1

2.00 [0.079]

16.00 [0.630]

**ADDITIONAL SPECIFICATIONS**

ANCHOR TUBE:  
PIPE: STEEL TUBE, ROUND,  
PER ASTM A500 GRADE B/C Fy=350MPa (50ksi) Min

WING:  
WING PLATE: MAT'L ASTM A1011 GRADE 33;  
Min Fy=230MPa(33ksi)

ALL WELDING ACCORDING TO CSA STANDARD W59-03

GALVANIZED TO ASTM A123/A123M-02

connecting area  
closed welded

SECTION A-A

Ø 35.00 ±5.00 [1.378 ±0.197]



DWG NO: <b>0005-176-76-4.2-3000</b>		REV. -
DRAWN: C.SENIS	DIMENSIONS : INCHES TOLERANCES: FRACTIONAL: ± 1/32 ANGULAR: ±1° 0.00: ± 0.015 0.000: ± 0.005 0.0000: ± 0.0005	
DATE: 7/5/2016	SCALE: 1:3	SIZE <b>B</b>
131 LAKE ROAD, BOWMANVILLE, ONT. CANADA, L1C 4P8		SHEET 1 OF 1