



$\phi 2.996\text{in} [76.1\text{mm}]$
 $0.142\text{in} [3.6\text{mm}]$
 $\phi 0.472\text{in} [12\text{mm}]$
 $2 \times \phi 0.709\text{in} [18\text{mm}]$

$\phi 19.291\text{in} [490\text{mm}]$

VIEW B
SCALE 1 : 4

ADDITIONAL SPECIFICATIONS
 ANCHOR TUBE:
 PIPE: STEEL TUBE, ROUND,
 PER ASTM A500 GRADE B/C $F_y=350\text{MPa}$ (50ksi) Min

WING:
 WING PLATE: MAT'L ASTM A1011 GRADE 33;
 Min $F_y=230\text{MPa}$ (33ksi)

ALL WELDING ACCORDING TO CSA STANDARD W59-03

GALVANIZED TO ASTM A123/A123M-02



DWG NO: 0005-490-76-3.6-3000		REV. -
DRAWN: C. WILSON	DIMENSIONS : INCHES	
DATE: 6/17/2016	TOLERANCES:	
SCALE: 1:5	SIZE B	FRACTIONAL: $\pm 1/32$
S:\MALINA\GROUND SCREWS\0005-490-76-3.6\		ANGULAR: $\pm 1^\circ$
SHEET		0.00: ± 0.015
1 OF 1		0.000: ± 0.005
		0.0000: ± 0.0005

SECTION A-A

$\phi 1.378\text{in} \pm 0.200 [35\text{mm} \pm 5.1]$