

Luxury Floors

Aloft™
Click and Glue Down



THE ULTIMATE
FLOORING EXPERIENCE

Tarkett® Luxury Floors – Aloft™ Click and Glue Down




32C0082 | 32C0082G Cooper's Oak Bay



32C0083 | 32C0083G Cooper's Oak Roan



32HM186 | 32HM186G Heart Maple Golden Rose



32IN401 | 32IN401G Jatoba Cayenne




32IN542 | 32IN542G Flamed Oak Pewter



32IN544 | 32IN544G Flamed Oak Canyon





32LDP151 | 32LDP151G Lodge Plank Gray Pearl



32LP1023 | 32LP1023G Long Pine Black & Tan

Features

- Water-, moisture-, drip-, spill- and splash resistant
- Warm, comfortable, and quiet
- 12 mil wear protection system
- Better indoor air quality
- Made with virgin raw materials
- 25 Year Limited Residential Warranty
- 7 Year Limited Light Commercial Warranty
- FloorScore® Certified
- Phthalate Free
- Matching Transitions and Stair Nosing Available



ALOFT™		
	CLICK	GLUE DOWN
Nominal Thickness	0.126" (3.2 mm)	0.080" (2.0 mm)
Wear Layer Finish	12 mil wear protection system	12 mil wear protection system
Plank Size	5.906" x 48.031" (15.0cm x 122cm)	6" x 48" (15.24cm x 121.92cm)
Sq. Ft. per Carton	27.58 sq. ft. (2.56 m ²)	36 sq. ft. (3.346 m ²)
Planks per Carton	14	18
Cartons per Pallet	60	78
Lbs. per Carton	34.17 lbs. (15.50 kg)	27.56 lbs. (12.50 kg)
ASTM E648 (Critical Radiant Flux)	> .45 w/cm ²	> .45 w/cm ²
ASTM E662 (Optical Smoke Density)	<450	<450
ASTM F1514 (Heat)	Δ E < 8	Δ E < 8
ASTM F1515 (Light)	Δ E < 8	Δ E < 8
ASTM F970 @250PSI (Static Load Limit)	Passes	Passes
Installation	Click	Glue Down - Tarkett recommended adhesive
Certification	FloorScore® Certification	FloorScore® Certification



THE ULTIMATE FLOORING EXPERIENCE

USA Residential: 1-877-TARKETT (1-877-827-5388). USA Commercial: 1-800-899-8916. Canada: 1-877-436-6267.

tarkettna.com